

ELECTRIC DRIVE SELF CLEANING WATER FILTER

FED200

FED200 · FED · DN 200 · Electric drive

Electric motor drive automatic filter. DN200. Flow rate 320 m³/h.

TECHNICAL DAT ASHEET



SCAN FOR PRODUCT PAGE

filtaworx.com/products/automatic-filters/fed200



KEY FEATURES

- Electric Gear Motor Drive
- Precise Backwash Control
- Self-Reversing Drive Shaft
- Suction Nozzle Cleaning
- Wide Pressure Range: 0.5–16 bar
- PLC Controller Integration

SPECIFICATIONS

Drive Type	Electric
Filter Size	DN200
Flow Rate	320 m ³ /h
Filtration Area	8,115 cm ²
Filtration Degree	30, 50, 80, 100, 120, 150, 200, 300, 400, 800 µm
Operating Pressure	0.5–16 bar
Max Temperature	65 °C
Rinse Cycle	15–17 seconds

02 • DIMENSIONS

Dimensions

TABLE 1 Data & Weights

Model	DN	Flowrate	Filter area	Weight (Std)	Weight (HP)
FED200	DN200	320 m ³ /h	8,115 cm ²	130 kg	320 kg (full)

TABLE 2 Dimensions

Dimension	Value
Inlet / Outlet	DN200 (8")
Body Ø	325 mm
Centre distance	900 mm
Body O/A length	2,050 mm
Filtration area	8,115 cm ²
Flow rate	320 m ³ /h (1,409 gpm)


TABLE 3 Shipping & weights

Item	Value
Packed dimensions (L x W x H)	280 x 55 x 76 cm
Shipping volume	1.2 m ³
Weight — standard	135 kg (300 lb)
Weight — high pressure	170 kg (375 lb)

03 • PERFORMANCE

Performance

PERFORMANCE Pressure Drop vs Flow



Curves: $dp(q) = r \cdot q^2$ across available screen sizes. Source per screen — 30 μm : estimated · 50 μm : estimated · 100 μm : estimated · 150 μm : estimated · 200 μm : estimated · 300 μm : estimated · 400 μm : estimated · 800 μm : estimated.

TYPICAL APPLICATIONS

Agriculture & Irrigation · Industrial Water · Water Sources · Cooling Towers · Food & Beverage · Mining

Filtaworx · Australian manufacturer of automatic self-cleaning filters

filtaworx.com/products/automatic-filters/fed200