




TECHNICAL DATA:

Normal Flow Rate: 793 GPM / 180 cubic m/hr at 2m Head Loss

Filter Area: 1257.83 sq in / 8115 sq cm

Screen Size Available: 50, 80, 100, 120, 150, 200, 400, 800 micron

Max. Working Pressure: 150psi / 10 bar

Min. Upstream Line Pressure Required During Rinse Cycle: 30 psi / 2 bar

Max. Working Temperature: 150°F / 65°C

Approximate Rinse Cycle Time: 15 - 17 Sec.



Inlet & Outlet Connection: DN150 Table E / ISO PN10 / ANSI CL150

Flush Drain Outlet Connection: 2" BSPT Male

Main Drain Header: DN50 2" Nominal Bore


Approximate Weight: Empty ----- 254 lbs / 115 kg

Full of Water --- 585 lbs / 265 kg



INLET

Flange Details Depend
Customer Selected Flange Type



OUTLET

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
FILTAWORX PTY. LTD. ANY REPRODUCTION
IN PART OR AS A WHOLE WITHOUT THE
WRITTEN PERMISSION OF FILTAWORX PTY.
LTD. IS PROHIBITED.


DIMENSIONS ARE IN [inches]/mm

MATERIAL
STAINLESS STEEL BODY
GLASS REINFORCED NYLON LID

FINISH

TOL. MACHINING ±0.25

TOL. ANGULAR ±0.25°



FILTAWORX

TITLE

FW150EX WATER FILTER
AUTOMATIC SELF CLEANING
DN150 TABLE E / ISO PN10 / ANSI CL150

SIZE

A3

DWG. NO.

GA-04708-H

REV.

0

SCALE: 1:10.

WEIGHT: SEE TECHNICAL DATA

SHEET: 1 OF 1