




TECHNICAL DATA:

Normal Flow Rate: 2641.72 GPM / 600 cubic m/hr at 2m Head Loss

Filter Area: 1614.33 sq in / 10415 sq cm

Screen Size Available: 50, 80, 100, 120, 150, 200, 400, 800 micron

Max. Working Pressure: 150psi / 10 bar

Min. Upstream Line Pressure Required During Rinse Cycle: 30 psi / 2 bar

Max. Working Temperature: 150°F / 65°C




Approximate Rinse Cycle Time: 15 - 17 Sec.

Inlet & Outlet Connection: DN300 Table E / ISO PN10 / ANSI CL150

Flush Drain Outlet Connection: 2" BSPT Male


Main Drain Header: DN50 2" Nominal Bore

Approximate Weight: Empty ----- 529 lbs / 240 kg
Full of Water --- 1212.5 lbs / 550 kg



INLET

Flange Details Depend
Customer Selected Flange Type



OUTLET


PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
FILTAWORX PTY. LTD. ANY REPRODUCTION
IN PART OR AS A WHOLE WITHOUT THE
WRITTEN PERMISSION OF FILTAWORX PTY.
LTD. IS PROHIBITED.

DIMENSIONS ARE IN [inches]/mm

MATERIAL
STAINLESS STEEL BODY
GLASS REINFORCED NYLON LID

FINISH

TOL. MACHINING ±0.25
TOL. ANGULAR ±0.25°



FILTAWORX

TITLE
FW300 WATER FILTER
AUTOMATIC SELF CLEANING
DN300 TABLE E / ISO PN10 / ANSI CL150

SIZE A3 DWG. NO. GA-05008-E REV. 0

SCALE: 1:12. WEIGHT: SEE TECHNICAL DATA SHEET: 1 OF 1